



FUSE: 13A
 RATING: 13A 250V
 INSULATING RESISTANCE: DC500V 100M OHM
 DIELECTRIC STRENGTH: AC 1000V/1 MINUTE

5	COVER	NYLON 6+15%GF	1
4	SCREW	STEEL	1
3	PLUGS	ALLOY COPPER	2
2	GROUND PIN	ALLOY COPPER	1
1	GROUND BASE	NYLON 6 +15%GF	1
ITEM NO.	DESCRIPTION	MATERIAL	QTY

INSIDE CONTACT: BRONZE C2680

TOLERANCES
0.5MM-5MM=±0.2MM
5MM-30MM=±0.4MM
30MM-120MM=±0.6MM
120MM-315MM=±1.0MM
315MM-1000MM=±1.6MM
1000MM-2000MM=±2.4MM

General Tolerance	繪圖 Draw By C.T. WANG	設計 Designed By T.H.HUANG	比例尺 Scale 1:1
版本 Version 3	核準 Approved By J.F.WANG	核準日期 Date 10 OCT 2008	單位 UNIT m/m

穩鈦興業有限公司
 WUN TAIX CO., LTD.

WTN-01-1154
 AC ADAPTOR
 250V 13A W/ FUSE
 British Type

REF.NO.