



SPECIFICATION

Dielectric strength: AC500 1 Minute
 Insulation resistance: 100M ohm at 500VDC
 Contact resistance: 30m ohm Max
 Rating: 3A

L SIZE:
 9.5MM OR 14MM
 ID SIZE:
 2.1MM OR 2.5MM

TOLERANCES	
0.5MM-5MM	± 0.2 MM
5MM-30MM	± 0.4 MM
30MM-120MM	± 0.6 MM
120MM-315MM	± 1.0 MM
315MM-1000MM	± 1.6 MM
1000MM-2000MM	± 2.4 MM

No.	Description	Material	Qty
1	Hexagon Handle	Plastic PE208	1
2	Contact	C2680 copper, Nickel	1
3	Plug	C3604 Alloy Copper, Nickel	1
4	Black tip	Derlin	1
5	Inside Insulation	Derlin+Fiber	2

WTN-27-1141C	2.1X5.5X9.5MM
WTN-27-1141D	2.5X5.5X9.5MM
WTN-27-1141E	2.1X5.5X14MM
WTN-27-1141F	2.5X5.5X14MM

General Tolerance	繪圖 Draw By C.T WANG	設計 Designed By C.T WANG	比例尺 Scale 1:1
版本 Version	核準 Approved By J.H. HUANG	核準日期 Date 7 Jul 2011	單位 UNIT m/m
2			

穩鈦興業有限公司 WUN TAIX CO., LTD.	WTN-27-1141 DC PLUG W/HEXAGON PLASTIC HANDLE	REF. NO.