



SPECIFICATION:

耐電壓Withstand voltage: AC 500V 60Hz for 1 minute
 絕緣阻抗Insulation resistance : 100MΩ (min) at 500V DC
 接觸阻抗Contact resistance : 50mΩ max
 定格Rating: 6A 125VAC

COLOR:
 RED(RD)/BALCK(BK)/BLUE(BU)/GREEN(GR)/YELLOW(YE)/WHITE(WH)

3	HOUSING(塑膠殼)	PA66	RD紅/BK黑/BU藍/ GN綠/YE黃/WH白	1
2	SPRING(九葉鍍銅)	BERYLLIUM COPPER	NICKEL(鍍鎳)/GOLD(鍍金)	1
1	PLUG(銅柱)	C3604 ALLOY COPPER	NICKEL(鍍鎳)/GOLD(鍍金)	1
NO	PART NAME(品名)	MATERIAL(材質)	FINISHED(外觀)	Q'TY

表面處理	比例尺 Scale	繪圖 DRAW BY	圖號	穩鈦興業有限公司 Wuntaix Co., LTD.	品號	WTN-06-1011	備註	No asscessory	TOLERANCES 0.5MM-5MM=±0.2MM 5MM-30MM=±0.4MM 30MM-120MM=±0.6MM 120MM-315MM=±1.0MM 315MM-1000MM=±1.6MM 1000MM-2000MM=±2.4MM
版本VERSION	單位 UNIT	核准 APPROVED BY	日期 DATE					TEL:06-2332589 FAX:06-2317778 http://www.wuntaix.com	
	mm	YACHAN WANG	2020/4/14			2MM			